

The Development of Design Methodology for High-performance Turbomachinery Blades and Components using Large-scale Aerodynamic and Structural Interaction Analysis including Off-design Condition

Project Representative

Hiroshi Saeki

Toshiba Corporation

Authors

Hiroshi Saeki^{*1}, Kenichi Okuno^{*1}, Tomohiko Tsukuda^{*1}, Daisuke Nomura^{*1}, Sakae Kawasaki^{*1}, Tadashi Tanuma^{*2}, Satoru Yamamoto^{*3}, Hiroshi Okuda^{*4}, Gaku Hashimoto^{*4}, Takao Kobayashi^{*5}, Keiji Suehiro^{*6}, Xi Yuen^{*6}, Yoshinari Fukui^{*7}, Yuichi Hirokawa^{*7}, Noriaki Nishikawa^{*7}, Misako Iwasawa^{*7}, Toshiyuki Asano^{*7}, Kumi Akiyama^{*8}

- * 1 Power and Industrial Systems Research and Development Center, Toshiba Corporation
- * 2 Applied Fluid Dynamics & Energy Machinery Systems, Joint Program Center, Teikyo University
- * 3 Dept. of Computer and Mathematical Sciences, Tohoku University
- * 4 Graduate School of Frontier Sciences, The University of Tokyo
- * 5 Toshiba Information Systems Corporation
- * 6 Advance Soft Corporation
- * 7 Japan Agency for Marine-Earth Science and Technology
- * 8 Office Kei Corporation

Abstract

Power generation systems that employ steam turbines produce more than 70% of the global supply of electricity, and the global electricity generation is projected to increase by a factor of about 1.7 by 2035. Consequently, the development and practical realization of technologies required to enhance the efficiency of steam turbines for power generation should be encouraged to meet the electricity demand while limiting and reducing global greenhouse gas emissions.

The aim of this project is to increase steam turbine efficiency with the development of design methodology for high-performance turbomachinery blades and components in particular steam turbine high-performance rotating blades and exhaust hoods using large-scale aerodynamic and structural interaction analysis including off-design condition.

Main components of steam turbines are turbine stages that consist with stator blades and rotating blades. Aerodynamic optimum designs of stator blades are already introduced in many designs of actual

operating commercial steam turbine units. However, aerodynamic optimum designs of rotating blades are still difficult due to high centrifugal force and vibration stress on rotating blades. The current project focuses on rotating blades and exhaust diffusers that affect the flow field just downstream of last stage long blades.

The large-scale high-accuracy CFD analysis of unsteady wet steam flows has been successfully introduced for simulations of low pressure exhaust diffuser using the Earth Simulator of Japan Agency for Marine-Earth Science and Technology.

The unsteady flow analyses using 360-degree whole circumference all stator and rotating blade flow path calculation domain of the typical designed last stage with the measured downstream static pressure distribution as the outlet boundary condition were conducted using package software on SGI UV2000 system. The blade outlet static pressure circumferential distribution caused non-negligible effect on the last stage unsteady flow characteristics in very low load operating condition.

The large-scale parallel computing Finite Element Analysis of turbine blades with inter-connection parts has been also successfully introduced on the Earth Simulator. The calculation result shows that the eigen frequencies of the present group of loosely-connected six rotating blades correspond well to the existing measured data. For the aerodynamic and structural interaction analysis, the software module that transfers the calculated data with CFD to the traction data for the rotating blade surface boundary conditions was developed and the accuracy of the software was verified using model turbine data. The large-scale structural analysis was successfully conducted using blade surface unsteady traction data that were translated from the unsteady aerodynamic analysis result.

Keywords: aerodynamic and structural interaction analysis, steam turbine, efficiency, blade, unsteady aerodynamic force